

## The Perfect Balance of Speed, Size, and Memory



**4,980fps @ 1920x1080 | 10GPx/s throughput | 10,000fps @ 1176x870**

### FEATURES + OPTIONS

- HD resolution 1920 x1080 pixel sensor, more pixels = greater accuracy
- Full resolution to 4,980 frames/second, maintaining higher res at higher speeds
- 8 TB internal SSD capacity
- Up to 144 GB of on-board memory for long recordings or multiple buffers
- Internal or external SSD drive for fast data transfer
- Impressive 10 GP/sec throughput
- Global electronic shutter to 250 ns\*
- Compatible with all Nikon F and Canon EF mount lenses
- Record up to 500,000 fps
- App-based tablet control via Controller Display Unit (CDU) for simple operation
- Fully compatible with the i-SPEED Software Suite 2.0 for more advanced functions
- Upgrade path between models

\* subject to export regulations

**High performance high-speed camera in a compact and durable form-factor.**



The sealed electronics design of the i-SPEED 5 utilizes an innovative internal cooling system—drawing heat from the inside of the camera and venting it to the atmosphere

**Sublime ease-of-use coupled with full feature functionality**



## IMAGER

<b>Sensor type</b>	Custom CMOS
<b>Sensor resolution</b>	1920 x 1080 pixel
<b>Sensor size</b>	25.920 mm x 14.580 mm
<b>Sensor diagonal</b>	29.74 mm
<b>Pixel size</b>	13.5 µm
<b>Bit depth</b>	12 bit (36 bit color)
<b>ISO (12232-2:2006, D, sat)</b>	Mono ISO 8,500D (sat) / 68,000D (sat) Color ISO 3,060D (sat) / 24,480D (sat)
<b>Maximum frame rate</b>	500,000 fps
<b>Shutter type</b>	Global exposure
<b>Shutter time, standard</b>	1 µs min (standard)
<b>Shutter time, fast mode</b>	250 ns min (export restricted)

## SYNCHRONIZATION and CAPTURE

<b>Trigger</b>	TTL T0 to 0-100%
<b>Trigger modes</b>	Circular, ROC, BROCC
<b>Sync</b>	10 Hz – 350 kHz
<b>Luminance histogram</b>	Iris setting aid tool
<b>i-CHEQ 360</b>	Camera status LEDs
<b>i-FOCUS</b>	Focusing aid tool
<b>i-EXPOSE</b>	High/low exposure highlight
<b>Control</b>	PC or CDUE
<b>IRIG input</b>	IRIG – B to 1 µs
<b>Internal memory</b>	18 GB standard, upgrade to 144 GB

## PHYSICAL and ENVIRONMENTAL

<b>Dimensions inches</b>	5.0 (W) x 5.1 (H) x 12.0 (L)
<b>Dimensions mm</b>	127 (W) x 129 (H) x 305 (L)
<b>Weight</b>	9.9 lb (4.5 kg)
<b>Input voltage</b>	14-36 V
<b>Power consumption</b>	110 W nominal, 150 W max
<b>Mounting</b>	1/4 x 20 and 3/8 x 16 tripod plate
<b>Lens mount</b>	Custom, swappable lens plate
<b>EMC</b>	EN55032-A, EN55024
<b>Safety</b>	BS EN61010-1 (camera), IEC60950 (PSU)
<b>CE marking</b>	EMC directive (camera), EMC directive, LV directive (PSU)
<b>Lead free</b>	RoHS directive
<b>WEEE</b>	Compliant
<b>Temperature °F</b>	14° to 122° operation, -4° to 140° storage
<b>Temperature °C</b>	-10° to +50° operation, -20° to 60° storage
<b>Pressure</b>	71 kpa to 106 kpa
<b>Relative humidity</b>	95% at 104°F non-condensing
<b>Power input connector</b>	4 pin Lemo
<b>Trigger input</b>	BNC 75 Ω
<b>I/O connector</b>	10 pin Lemo, trigger in / sync / exposure out / remote power

## CONNECTIVITY

<b>Video outputs</b>	HD-SDI, HDMI
<b>USB</b>	USB 3
<b>Network</b>	1Gb/s RJ45 / 10 pin Lemo
<b>Video</b>	IXV, AVI (compressed or uncompressed)
<b>Image sequence</b>	TIFF, JPG, RAW
<b>Ethernet control</b>	1 Gb/s
<b>Remote control</b>	Via supplied software

## PC SOFTWARE

<b>Standard control</b>	Control ONE
<b>Premium control</b>	Control MULTI-DAQ
<b>Editing</b>	i-SPEED Movie Maker
<b>Analysis</b>	ProAnalyst® Lite by Xcitex
<b>Viewer</b>	i-SPEED Viewer
<b>Utilities</b>	i-SPEED Lens Calculator, i-SPEED Viewer
<b>Software Developers Kit</b>	C++, LabView
<b>Synchronized data acquisition</b>	USB DAQ, 8 options

## PURCHASING OPTIONS

<b>CDUE</b>	Controller Display Unit
<b>Sensor</b>	Color / Mono
<b>Memory</b>	18 GB (std) / 36 GB / 72 GB / 96 GB / 144GB
<b>Shutter time</b>	1 µs (std) / 250 ns (subject to export restrictions)
<b>Internal SSD</b>	500 GB / 1 TB / 2 TB / 4 TB / 8 TB
<b>External SSD</b>	500 GB / 1 TB / 2 TB
<b>Lens mounts</b>	F mount (Nikkor D) / F mount (Nikkor G) C mount / EF mount
<b>Warranty</b>	1 yr (std) / 2 yr / 3 yr
<b>IRIG</b>	IRIG-B

## FRAME RATES, RESOLUTION, and DURATION

FPS	Resolution	18GB	36GB	72GB	96GB	144GB
100	1920x1080	60.85	121.70	243.40	324.53	486.80
200	1920x1080	30.43	60.85	121.70	162.27	243.40
300	1920x1080	20.29	40.57	81.14	108.19	162.28
500	1920x1080	12.17	24.34	48.68	64.91	97.36
1,000	1920x1080	6.09	12.17	24.34	32.45	48.68
2,000	1920x1080	3.04	6.09	12.17	16.23	24.34
3,000	1920x1080	2.03	4.06	8.11	10.82	16.22
3,985	1920x1080	1.53	3.05	6.10	8.13	12.20
4,980	1920x1080	1.22	2.44	4.89	6.51	9.77
5,000	1904x1080	1.25	2.51	5.01	6.68	10.02
6,382	1512x1080	1.24	2.47	4.94	6.59	9.88
7,500	1344x1008	1.27	2.54	5.07	6.76	10.14
10,000	1176x870	1.26	2.52	5.04	6.71	10.07
15,000	952x708	1.27	2.55	5.10	6.79	10.19
20,000	840x594	1.29	2.58	5.16	6.88	10.32
50,000	504x366	1.40	2.79	5.58	7.44	11.16
100,000	392x204	1.61	3.22	6.44	8.59	12.88
200,000	392x90	1.83	3.65	7.30	9.73	14.60
300,000	392x54	2.03	4.05	8.10	10.80	16.20
500,000	392x24	2.74	5.47	10.94	14.59	21.88

Note: Other resolutions and speeds are available.



info@ix-cameras.com • ix-cameras.com

Specifications subject to change  
Document: DS-510-02.08.19 Copyright © 2019 iX Cameras Ltd.

### United Kingdom

iX Cameras  
Bradley House  
Locks Hill  
Rochford  
Essex, SS4 1BB  
T: +44 (0) 1702 540 669

### United States

iX Cameras  
8 Cabot Rd.  
Suite 1800  
Woburn,  
MA, 01801  
T: 339 645 0778

### China

iX Cameras  
Room 1402, Unit 65,  
No 399 Hanging Road,  
Oriental Hong Jing Garden,  
ZhuQiao Town, Shanghai,  
T: +86 186 215 60553

### India

iX Cameras  
J2-101  
Swiss County Thergaon  
Pune,  
411033  
T: 0955 256 5021